

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B65D 45/32, 43/04	A1	(11) International Publication Number: WO 00/69741 (43) International Publication Date: 23 November 2000 (23.11.00)
<p>(21) International Application Number: PCT/GB00/01765</p> <p>(22) International Filing Date: 9 May 2000 (09.05.00)</p> <p>(30) Priority Data: 9911063.7 12 May 1999 (12.05.99) GB</p> <p>(71)(72) Applicant and Inventor: <i>100</i> SHOWERING, Francis [GB/GB]; The House on the Shore, Thorns Beach, Beaulieu, Brockenhurst, Hampshire SO42 7XN (GB). <i>GB</i></p> <p>(74) Agent: HOLMES, Miles, Keeton; D. Young & Co., 21 New Fetter Lane, London EC4A 1DA (GB).</p>	<p>(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p>Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p>	

(54) Title: CONTAINER CLOSURE

(57) Abstract

A press-fit container closure (14) includes a plurality of depending segmented lugs (20) with snap-fit projections for engaging behind the rim of a container mouth. An integral band (30) embraces the lugs to lock the closure (14) securely on the container mouth. To remove the closure (14), the band (30) is lifted away (e.g. pivoted upwards). The lugs (20) are then free to flex outwardly, allowing the closure (14) to be lifted off the container mouth. The band (30) may be secured to the lugs (20) by frangible connections (34) to provide a tamper evident feature. One or more predetermined lugs (20a) may be designed to be released prior to other lugs during opening, to vent internal pressure from within the container while the remaining lugs hold the closure securely and prevent the closure from blowing off the container mouth.



209740 90E6000T